DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 20 N., R. 30 E., MDM, NEVADA

CHAIN

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T20N R30E $\frac{1}{4}$ S 33|S 34

1979

bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.

N. 0° 17' W., bet. secs. 32 and 33.

Over nearly level land, covered with sagebrush and native grass.

20.02 Point for the S 1/16 sec. cor. of secs. 32 and 33.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S 1/16

S 32|S 33

1979

set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

40.04

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a basalt stone, $14 \times 12 \times 3$ ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T2 ON R3 OE $\frac{1}{4}$ S 32 | S 33

1979

bury the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

SUBDIVISION OF SECTION 35, T. 20 N., R. 30 E., MDM, NEVADA