

DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 46 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R46E

$\frac{1}{4}$

S 31S 2

1979

Bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $1^{\circ} 32'$ E., beginning new measurement.

Over gently rolling land.

39.89 Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R46E

S 34

S 31S 2

T10N R46E

CC

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 34 and 35, T. 11 N., R. 46 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 11 N., R. 46 E., executed concurrently under this same group, bears S. $87^{\circ} 27'$ E., 11.07 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 is at midpoint bet. the closing cors. and on the S. bdy. of sec. 35, T. 11 N., R. 46 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2

T10N R46E

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.