

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 11 N., R. 46 E., MDM, NEVADA

CHAINS

A pinon pine, 14 ins. diam., bears N. $74 \frac{3}{4}^{\circ}$ E.,
21 lks. dist., mkd. $\frac{1}{4}$ S18 BT on a partially healed
blaze.

A pinon pine, 6 ins. diam., bears S. $18 \frac{1}{4}^{\circ}$ E., 27
lks. dist., mkd. $\frac{1}{4}$ S18 BT on a partially healed
blaze.

Remark the brass cap as follows:

|T11N
|R46E
| $\frac{1}{4}$
|S 18

1979

1938

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES,
T. 11 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
D.H. Barker, U.S. Deputy Surveyor,
in 1874,
and a Portion of the Resurvey Executed by
Emil Voigt, Cadastral Engineer,
J.W. Hardison and J.G. Dyer, Public Land Surveyors,
in 1938.

From the standard cor. of secs. 35 and 36, on the S.
bdy. of the Tp.

N. $1^{\circ} 07'$ E., bet. secs. 35 and 36.

Over nearly level land, covered with medium rabbitbrush,
greasewood, sagebrush and native grass.

39.86 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at
proportionate distance; there is no remaining evidence
of the original corner.

Set an iron post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T11N R46E
 $\frac{1}{4}$
S 35|S 36

1979

Raise a mound of stone, 3 ft. base, $1 \frac{1}{2}$ ft. high, W. of
cor.

79.72 The cor. of secs. 25, 26, 35 and 36, monumented with a
porphyry stone, 17x4x3 ins., plainly mkd. with 1 groove
on S. and E. faces, firmly set 7 ins. in a mound of
earth.

At the corner point

Set an iron post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.