

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 12 N., R. 46 E., MDM, NEVADA

CHAINS	
	<p>N. 1° 08' E., beginning new measurement.</p> <p>Over nearly level land.</p>
27.30	<p>Trail road, bears ENE. and WSW.</p>
39.68	<p>The original cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 16x12x8 ins., firmly set and exposed 12 ins. above the ground, plainly mkd. with 5 notches on the S. edge and 1 notch on the N. edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R46E R47E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1979</p> <p>Bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
39.65	<p>N. 1° 06' E., bet. secs. 1 and 6.</p> <p>Over nearly level land, through rabbitbrush and greasewood.</p> <p>The original ¼ sec. cor. of secs. 1 and 6, monumented with a granite stone, 16x10x7 ins., firmly set and exposed 10 ins. above the ground, plainly mkd. with ¼ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R46E R47E ¼ S 1 S 6</p> <p style="text-align: center;">1979</p> <p>Bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 1° 09' E., beginning new measurement.</p> <p>Over nearly level land.</p>