DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 28 N., R. 48 E., MDM, NEVADA

CHAINS

N. 0° 34' E., bet. secs. 1 and 6.

Over nearly level land, covered with sagebrush.

9.40 Trail road, bears NW. and SE.

40.10 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a granite stone, $20 \times 10 \times 8$ ins., plainly mkd. $\frac{1}{4}$ on the W. face, firmly set and exposed 8 ins. above ground, with a steel fence post alongside.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T28N R48E R49E · ¹/₄ S 1|S 6

1979

bury the original cornerstone and reset the steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet set in a concrete post, 6 ins. square, exposed 1 ft. above ground, with cap mkd. "39 GWM 1937 4748," bears N. 67° 41' W., 40.64 chs. dist.

N. 0° 33' E., beginning new measurement.

Over nearly level land, covered with sagebrush.

15.60 Gravel road, bears E. and W.

The cor. of Tps. 28 and 29 N., Rs. 48 and 49 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 29 N., R. 48 E., executed concurrently under this same group.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 28 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by A.J. Hatch and J.H. Eaton, U.S. Deputy Surveyors, in 1869.

From the cor. of secs. 3, 4, 33 and 34, on the south bdy. of the Tp., monumented with a juniper post, 3 ins. diam., 3 ft. long, loosely set in a mound of stone, mkd. with 3 notches on the E. and W. faces.