

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 28 N., R. 48 E., MDM, NEVADA

CHAINS	
	N. 88° 56' W., bet. secs. 5 and 32.
	Over gently rolling land, covered with sagebrush.
3.80	Trail road, bears NE. and SW.
19.00	Fence, bears NE. and SW.
36.00	Fence, bears NW. and SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T28N R48E \\ S 32 \\ \frac{1}{4} \hline S 5 \\ T27N \end{array}$
	1979
	set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
56.00	Trail road, bears NW. and SE.
79.60	Telephone line, bears N. and S.
80.00	The cor. of secs. 5, 6, 31 and 32, monumented with a decayed wooden post, 2 ins. square, 12 ins. long, wired to a steel fence post, firmly set 16 ins. in the ground.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T28N R48E \\ S 31 S 32 \\ S 6 S 5 \\ T27N \end{array}$
	1979
	bury the original wooden post and reset the steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
	From this corner, a spring, 1 ch. in diam., draining NE., bears N. 65° 56' E., 18.60 chs. dist.
	N. 87° 56' W., bet. secs. 6 and 31.
	Over nearly level land, covered with sagebrush.