

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 28 N., R. 48 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T28N
R47E R48E
 $\frac{1}{4}$
S 1|S 6

1979

reset the wooden post and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. $0^{\circ} 29'$ W., beginning new measurement.

Over nearly level land, covered with sagebrush.

11.50 Gravel road, bears WNW. and ESE.

41.07 The cor. of Tps. 28 and 29 N., Rs. 47 and 48 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 29 N., R. 47 E., executed under Group No. 25.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A.J. Hatch and J.H. Eaton, U.S. Deputy Surveyors,
in 1869.

From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, determined at record bearing and distance from the cor. of secs. 13, 14, 23 and 24; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T28N, R48E
 $\frac{1}{4}$
S 23|S 24

1979

set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

NORTH, bet. secs. 23 and 24.

Over nearly level land, covered with sagebrush.