

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 N., R. 48 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 29 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U. S. Deputy Surveyors A. J. Hatch and J. H. Eaton,
in 1869

The cor. of Tps. 28 and 29 N., Rs. 48 and 49 E., monu-
mented with a sandstone, 18 x 10 x 6 ins., plainly
mkd. with 6 grooves on the north, east, south and west
faces, firmly set in a mound of earth, with a steel fence
post, firmly set and exposed 18 ins. above the ground
alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T29N
R48E R49E
S 36 S 31
S 1 S 6
T28N

1978

bury the original cornerstone, reset the steel fence
post and set a steel fence post, 5½ ft. long, 22 ins.
in the ground, alongside the iron post.

N. 88° 24' W., bet. secs. 1 and 36.

Over nearly level land, through sagebrush.

40.11 Point for the ¼ sec. cor. of secs. 1 and 36, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground, with brass cap mkd.

T29N R48E
S 36
¼ ——— S 1
T28N

1978

set a steel fence post, 5½ ft. long, 22 ins. in the
ground, alongside the iron post.

42.60 Bladed road, bears N. and S.