DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 29 N., R. 48 E., MDM, NEVADA

40.14

The cor. of Tps. 28 and 29 N., Rs. 47 and 48 E., monumented with an iron post, 3 ins. in diam., firmly set, and exposed 12 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 29 N., R. 47 E., executed under Group No. 25.

DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 29 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by U. S. Deputy Surveyors D. H. Barker and E. C. McClellan, in 1879

and the Resurvey Executed by U.S. Deputy Surveyor S. T. Morse, in 1901

From the cor. of Tps. 28 and 29 N., Rs. 48 and 49 E.

N. 0° 04' W., bet. secs. 31 and 36.

Over nearly level land, through sagebrush.

40.02

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a granite stone, $14 \times 10 \times 5$ ins., plainly mkd. $\frac{1}{4}$ on the W. face, firmly set and exposed 7 ins. above the ground, with a steel fence post firmly set alongside.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N R48E R49E 14 S 36 S 31

1978

bury the original cornerstone and reset the steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.

N. 0° 06' W., beginning new measurement.

Over nearly level land, through sagebrush.

40.06

The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, $18 \times 16 \times 12$ ins., plainly mkd. with 1 notch on the S. edge and 5 notches on the N. edge, firmly set and exposed 8 ins. above the ground, with a steel fence post firmly set alongside.