

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 29 N., R. 48 E., MDM, NEVADA

| CHAINS | | |
|--------------|--|--|
| | <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E R49E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1978</p> <p>bury the original cornerstone and reset the steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>From this corner, U.S.G.S. triangulation station "CRES", hereinbefore described, bears S. 77° 29' W., 63.26 chs. dist.</p> | |
| | <p>N. 0° 15' W., bet. secs. 1 and 6.</p> <p>Over gently rolling land, through sagebrush; asc. 100 ft. over a S. slope.</p> | |
| <p>40.08</p> | <p>The ¼ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 12 x 12 x 6 ins., plainly mkd. ¼ on the W. face, firmly set and exposed 8 ins. above ground, with a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E R49E ¼ S 1 S 6</p> <p style="text-align: center;">1978</p> <p>bury the original cornerstone and reset the steel fence post, 5½ ft. long, 10 ins. in the ground, alongside the iron post.</p> <p>N. 0° 06' W., beginning new measurement.</p> <p>Over rolling land, through sagebrush; asc. 125 ft. over a S. slope.</p> | |
| <p>32.00</p> | <p>Spur, slopes SE.; desc. 140 ft. over a NE. slope.</p> | |