18

DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 29'N., R. 48 E., MDM, NEVADA

		T. 29 N., R. 48 E., MDM, NEVADA
	CHAINS	
	18.60	Fence corner, from which fences bear N. and W.
	40.02	The N. ½ sec. cor. of sec. 5, monumented with an iron post, 1 in. diam. This iron post was rusted off at ground level, with a 12 in. piece lying alongside, mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 30 N., R. 48 E., executed under Group No. 25.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a fence bearing E. and W., with brass cap mkd.
a	1. .	4 S 5 T29N R48E
		1978
		and the second
	a sa ang sa	bury the original corner alongside the iron post.
		S. 89° 07' W., beginning new measurement.
		Over nearly level land, along fence.
	5.50	Nevada State Highway No. 21, bears N. 25° E. and S. 25° W.
	18.14	Point for the S. ½ sec. cor. of sec. 32, T. 30 N., R. 48 E., at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a fence bearing E. and W., with brass cap mkd.
	•.	T30N R48E <u>4 S 32</u>
		1978
	40.02	The cor. of secs. 5 and 6, monumented with an iron post, 3 ins. diam., firmly set and exposed 12 ins. above the ground, mkd. as described in the field notes of the
		dependent resurvey of the S. bdy. of T. 30 N., R. 48 E., executed under Group No. 25. This corner is located at a fence cor., from which fences bear S. and E.
		S. 89° 07' W., along the N. bdy. of sec. 6.
:		Over nearly level land, through sagebrush.
· .		

.