

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 48 E., MDM, NEVADA

CHAINS	
90.44	<p>The cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. in diam., firmly set and exposed 12 ins. above ground, mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 29 N., R. 47 E., executed under Group No. 25.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 05' W., bet. secs. 29 and 30.</p> <p>Over nearly level land, through sagebrush.</p>
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a basalt stone, 10 x 6 x 4 ins., plainly mkd. $\frac{1}{4}$ on the W. face, firmly set and exposed 4 ins. above ground. (Record, wooden post).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E $\frac{1}{4}$ S 30 S 29</p> <p style="text-align: center;">1978</p>
	<p>bury the original cornerstone and set a steel fence post, 5$\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>N. 0° 04' W., beginning new measurement.</p> <p>Over nearly level land.</p>
13.00	<p>Improved gravel road, bears NNE. and SSW.</p>
40.22	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 8 x 6 x 4 ins., mkd. with 2 notches on the S. edge and 5 notches on the E. edge, firmly set and exposed 4 ins. above the ground. (Record, wooden post).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E S 19 S 20 S 30 S 29</p> <p style="text-align: center;">1978</p>
	<p>bury the original cornerstone and set a steel fence post, 5$\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.</p>