

DEPENDENT MESURVEY OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 48 E., MDM, NEVADA

CHAINS	
88.44	<p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>The cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. in diam., firmly set and exposed 12 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 29 N., R. 47 E., executed under Group No. 25.</p>
40.07	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 51' E., bet. secs. 19 and 20.</p> <p>Over nearly level land, through sagebrush.</p> <p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E ¼ S 19 S 20 1978</p>
80.14	<p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>The cor. of secs. 17, 18, 19 and 20, monumented with a mound of stone. No marked stone found. This point is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29N R48E S 18 S 17 S 19 S 20 1978</p>
	<p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post, and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89° 36' W., bet. secs. 17 and 20.</p> <p>Over nearly level land, through sagebrush.</p>