

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
T. 14 S., R. 48 E., MDM, NEVADA

CHAINS 39.00	Spur, slopes SE.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on bedrock over a cross (X) and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R48E $\frac{1}{4}$ S 35 S 36</p> <p style="text-align: center;">1979</p> <p>set a steel fence post, 6 ft. long, alongside the iron post.</p>
50.00	Wash, 1 ch. wide, 2 ft. deep, drains SE.
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R48E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">1979</p> <p>set a steel fence post, 6 ft. long, 12 ins. in the ground, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy and volcanic ash. Timber, none; undergrowth, creosote bush, shadscale and cactus.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, exposed 6 ins. above ground and mkd. as described in the field notes of the independent resurvey of the E. bdy. of T. 14 S., R. 48 E., executed under Group No. 368.</p> <p>S. $89^{\circ} 57'$ W., bet. secs. 25 and 36.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
10.00	Wash, 10 lks. wide, $\frac{1}{2}$ ft. deep, drains SE.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.