DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH, THROUGH R, 44 E, MDM, NEVADA

CHAINS

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SC T16N R44E ½ S 31

1979

reset the remains of the wooden post alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 45' W., beginning new measurement.

Over gently rolling land.

The standard cor. of Tps. 16 N., Rs. 43 and 44 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., exposed 4 ins. above the ground, with brass cap mkd. as described in the remonumentation notes of certain corners in T. 16 N., R. 44 E., executed under Group No. 393, identical with triangulation station "JOE" of the Nevada Planning Division of the Nevada State Highway Department, and is at latitude 39° 11' 57.47" N. and longitude 117° 04' 58.00" W.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF T. 16 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by A.J. Hatch, D.H. Barker, and E.L. Bridges, U.S. Deputy Surveyors, in 1873.

From the standard cor. of Tps. 16 N., Rs. 44 and 45 E.

N. 0° 26' E., bet. secs. 31 and 36.

Over gently rolling marshy land, through scattered sagebrush, greasewood, rabbitbrush, willows and native grass.

40.00

The original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with the decayed remains of a shaved wooden post, 10 ins. long, 1 in. diam., loosely set in a mound of earth, with illegible scribe marks visible.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.