

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 16 N., R. 44 E., MDM, NEVADA

CHAINS

N. 0° 02' E., beginning new measurement.

Over nearly level land.

- 39.86 The original cor. of Tps. 16 and 17 N., Rs. 44 and 45 E., monumented with a squared wooden post, 24 ins. long, 2 ins. square, with illegible scribe marks visible, firmly set alongside a granite stone, 15x6x6 ins., firmly set and exposed 8 ins. above the ground, plainly mkd. with 6 notches on the N., S., E. and W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T17N
R44E R45E
S 36 | S 31
S 1 | S 6
T16N

1979

reset the wooden post, bury the stone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF
T. 16 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
C.C. Tracy, U.S. Deputy Surveyor,
in 1867,
and Resurveyed by Clinton Gurnee, U.S. Deputy Surveyor,
in 1905.

From the standard cor. of Tps. 16 N., Rs. 43 and 44 E.

N. 0° 20' E., bet. secs. 31 and 36.

Over rolling land, through scattered sagebrush, shadscale, and native grass.

- 16.10 Paved road to the town of Kingston, bears NW. and SE.

- 39.64 The original ¼ sec. cor. of secs. 31 and 36, monumented with a granite stone, 16x6x9 ins., plainly mkd. ¼ on W. face, firmly set and exposed 10 ins. above the ground alongside an iron pipe, 2 ins. diam., exposed 12 ins. above the ground, with brass plate on top mkd. T16N R43ER44E ¼ S 31 S 36 RLS 2999.

At the corner point