

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF  
T. 16 N., R. 44 E., MDM, NEVADA

CHAINS  
39.83

The cor. of secs. 19, 24, 25 and 30, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., exposed 8 ins. above the ground and in a collar of stone to cap, 3 ft. base, with brass cap mkd. as described in the field notes of the remonumentation of certain corners in T. 16 N., R. 44 E., executed under Group No. 393. This cor. will now refer to the cor. of secs. 24 and 25, T. 16 N., R. 43 E., only.

Remark the brass cap to read as follows:

T16N  
R43E R44E  
S 24 | S 19  
S 25 |

1979  
1961

N.  $0^{\circ} 04'$  E., bet. secs. 19 and 24.

Over mountainous land, through scattered juniper, pinon, sagebrush and native grass.

39.87 The original  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, monumented with a limestone,  $28 \times 4 \times 4$  ins., firmly set in a mound of stone, plainly mkd.  $\frac{1}{4}$  on W. face. This cor. will now refer to the  $\frac{1}{4}$  sec. cor. of sec. 24, T. 16 N., R. 43 E., only.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.

T16N |  
R43E |  
 $\frac{1}{4}$  |  
S 24 |

1979

bury the cornerstone alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF  
T. 16 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by  
A.J. Hatch, D.H. Barker and E.L. Bridges,  
U.S. Deputy Surveyors, in 1873,  
and a Portion of the Survey Executed by  
Thurtell and Kearney, U.S. Deputy Surveyors,  
in 1909.