

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
T. 16 N., R. 44 E., MDM, NEVADA

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.

T17N R44E
S 32
 $\frac{1}{4}$ S 5
T16N

1979

bury the cornerstone and set a steel fence post, 5 ft. long, 14 ins. in the ground, alongside the aluminum post.

N. $89^{\circ} 41'$ W., beginning new measurement.

Over mountainous land; asc. 530 ft. over broken SE. slope.

40.07 The original cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 23x8x8 ins., firmly set in a mound of stone, plainly mkd. with 5 notches on E. edge and 1 groove on W. face.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.

T17N R44E
S 31 | S 32
S 6 | S 5
T16N

1979

bury the cornerstone alongside the aluminum post.

DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES OF
T. 16 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
A.J. Hatch, D.H. Barker, and E.L. Bridges,
U.S. Deputy Surveyors,
in 1873.

From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.

N. $0^{\circ} 42'$ E., bet. secs. 35 and 36.

Over gently rolling land, through scattered sagebrush, greasewood and shadscale.