

DEPENDENT RESURVEY OF  
A PORTION OF THE SUBDIVISIONAL LINES,  
T. 23 N., R. 20 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R20E ¼ S 30</p> <p style="text-align: center;">1980</p>
	<p>raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p> <p>38.96 The witness ¼ sec. cor. of secs. 30 and 31, monumented with a granite stone, 17x12x8 ins., firmly set 12 ins. in the ground, mkd. WC ¼ on N. face, with a mound of stone N.; hereafter this corner will refer to sec. 31 only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WC ¼ S 31 T23N R20E</p> <p style="text-align: center;">1980</p> <p>deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 2 ft. base, 1½ ft. high, S. of cor.</p> <hr/> <p>S. 89° 52' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
1.00	True point for the ¼ sec. cor. of sec. 31, at proportionate distance falls in draw, where it is impracticable to perpetuate a permanent monument.
15.50	Trail road, bears NNE. and SSW.
39.80	Fence, bears NE. and SW., 23 lks. dist. to fence cor., from which fences bear NE. and S.
39.92	<p>The cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with a granite stone, 16x10x8 ins., firmly set in a mound of stone, mkd. with 1 groove on S. face and 5 grooves on N. face, with a wooden post, 2 ins. square, 14 ins. long, mkd. R19E on W. face, R20E on E. face and illegible scribing on other 2 faces, set alongside.</p> <p>At the corner point</p>