DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 23 N., R. 20 E., MDM, NEVADA

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N R20E S 9|S 10 S 16|S 15

1980

deposit the original cornerstone alongside the iron post.

COMPLETION SURVEY OF SECTIONS 22 AND 27, T. 23 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

From the cor. of secs. 27 and 28.

N. 0° 02' E., bet. secs. 27 and 28.

Over mountainous land, covered with sagebrush and scattered juniper.

Ascend over broken S. slope.

40.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, determined at 40.00 chs. in latitude from the cor. of secs. 30 and 31, on the W. bdy. of the Tp.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N R20E $\frac{1}{4}$ S 28|S 27

1980

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

- 65.50 Spur, slopes E.; desc. over NE. slope, changing to E. slope.
- 80.11 Point for the cor. of secs. 21, 22, 27 and 28, determined at 80.00 chs. in latitude from the cor. of secs. 30 and 31, on the W. bdy. of the Tp.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N R20E S 21|S 22 S 28|S 27

1980

raise a mound of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, W. of cor.