

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 5 N., R. 46 E., MDM, NEVADA

CHAINS

Bury the cornerstone and set a steel fence post, 5 ft. long, alongside the aluminum post.

N. 0° 07' W., beginning new measurement.

Over mountainous land, desc. 90 ft. over N. slope.

4.60 Wash, 10 lks. wide, 2 ft. deep, drains WNW.; asc. 290 ft. over broken ledgy S. slope.

39.01 The original cor. of secs. 19, 24, 25 and 30, monumented with a lava stone, 18 X 14 X 10 ins., firmly set in a mound of stone, plainly mkd. 2 grooves on S. face and 4 grooves on N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.

T5N
R45E R46E
S 24 | S 19
S 25 | S 30

1980

Bury the cornerstone and set a steel fence post, 5 ft. long, 6 ins. in the ground, alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 5 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
N.L. Berdan, U.S. Deputy Surveyor,
in 1883.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. 0° 10' E., bet. secs. 33 and 34.

Over rolling land, through scattered sagebrush and greasewood.

20.095 Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set an aluminum post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone to cap, 4 ft. base, with aluminum cap mkd.

S 1/16
S 33 | S 34

1980

Set a steel fence post, 5 ft. long, alongside the aluminum post.