

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

Reestablishment of the Survey Executed by
D. H. Barker and W. W. Skinner,
U. S. Deputy Surveyors,
in 1875.

The cor. of Tps. 18 and 19 N., Rs. 44 and 45 E.,
monumented with a granite stone, 24x12x12 ins., plainly
mkd. with 6 notches on the N., S., E. and W. edges,
firmly set 15 ins. in the ground, with a mound of stone
W. of the cor.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18
ins. in the ground to bedrock and in a mound of stone, 3
ft. base to top, with aluminum cap mkd.

T19N
R44E R45E
S 36 | S 31
S 1 | S 6
T18N

1979

Bury the original cornerstone alongside the aluminum
post.

N. $1^{\circ} 06'$ E., bet. secs. 31 and 36.

Over rolling land, through sagebrush and grass.

41.25 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a
trap stone 17x9x6 ins., plainly mkd. $\frac{1}{4}$ on the W. face,
firmly set 12 ins. in the ground, with a mound of stone
W. of the cor.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16
ins. in the ground to bedrock and in a mound of stone, 4
ft. base to top, with aluminum cap mkd.

T19N
R44E R45E
 $\frac{1}{4}$
S 36 | S 31

1979

Bury the original cornerstone alongside the aluminum
post, and set a wooden post, 6 ft. long, 3 ins. diam.,
alongside the aluminum post.