

37

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T19N
R44E R45E
 $\frac{1}{4}$
S 1|S 6

1979

Bury the original cornerstone and reset the steel fence post, 24 ins. in the ground, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 29'$ E., beginning new measurement.

Over rolling land.

20.10 Grass Valley Road, bears NE. and SW.

35.80 Trail road, bears NE. and NW.

39.88 The cor. of Tps. 19 and 20 N., Rs. 44 and 45 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 18 ins. above the ground, with a wooden post painted U S BM alongside, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 20 N., R. 45 E., executed under Group No. 72.

From this corner, U.S.C. & G.S. triangulation station "DORY," monumented with a standard brass tablet, firmly set in concrete, exposed 4 ins. above the ground, bears S. $1^{\circ} 48'$ E., 2.76 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

Reestablishment of the Survey Executed by
D. H. Barker and W. W. Skinner,
U. S. Deputy Surveyors, in 1875
and the Resurvey and Survey Executed by
H. Thurtell and W. Kearney,
U. S. Deputy Surveyors, in 1909.

From the cor. of Tps. 18 and 19 N., Rs. 44 and 45 E.

N. $89^{\circ} 46'$ W., bet. secs. 1 and 36.

Over mountainous land, through scattered sagebrush.

26.90 Spur, slopes SSE.