

DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

38.83

The cor. of secs. 32 and 33, monumented with a granite stone, 20x5x5 ins., plainly mkd. with 4 notches on the E. face and 2 notches on the W. face, firmly set 10 ins. in the ground, with a steel fence post, firmly set alongside and a mound of stone N. of cor.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

T19N R44E

S 32 | S 33

S 4

T18N

1979

Bury the original cornerstone and reset the steel fence post alongside the aluminum post.

From this corner, a spring bears S. $70^{\circ} 03'$ E., 8.76 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF
THE NORTH BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

Reestablishment of the Survey Executed by
D. H. Barker and W. W. Skinner,
U. S. Deputy Surveyors, in 1875
and the Resurvey and Survey Executed by C. Gurnee,
U. S. Deputy Surveyor, in 1905.

From the cor. of Tps. 19 and 20 N., Rs. 44 and 45 E.

N. $89^{\circ} 36'$ W., bet. secs. 1 and 36.

Over rolling land, through scattered sagebrush, juniper and pinon pine.

12.00 Trail road, bears NW. and SE.

30.00 Trail road, bears ENE. and WSW.

39.84 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a quartzite stone, 14x6x6 ins., plainly mkd. $\frac{1}{4}$ on the N. face, firmly set 8 ins. in the ground, with a steel fence post, firmly set alongside the cor.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.