

47

DEPENDENT RESURVEY OF A PORTION OF
THE NORTH BOUNDARY,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

N. 89° 58' W., bet. secs. 3 and 34.

Over rolling land, through scattered sagebrush.

40.19 The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a lava stone, 16x16x10 ins., plainly mkd. $\frac{1}{4}$ on the N. face, firmly set 8 ins. in the ground, with a mound of stone N. of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with aluminum cap mkd.

T20N R44E
 S 34
 $\frac{1}{4}$ S 3
T19N

1979

Bury the original cornerstone alongside the aluminum post and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

WEST, beginning new measurement.

Over mountainous land.

25.00 Spur, slopes SSW.

40.01 The cor. of secs. 3, 4, 33 and 34, monumented with a granite stone, 16x8x6 ins., plainly mkd. with 3 notches on the E. and W. edges, firmly set 8 ins. in the ground, with a mound of stone W. of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T20N R44E
S 33 | S 34
S 4 | S 3
T19N

1979

Bury the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 19 N., R. 44 E., MDM, NEVADA
