

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS
40.05

The cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 14x12x6 ins., plainly mkd. with 4 notches on the S. and E. edges, firmly set 8 ins. in the ground.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T19N R44E
S 8 | S 9
S 17 | S 16

1979

Bury the original cornerstone alongside the aluminum post.

From the cor. of secs. 9, 10, 15 and 16.

S. 89° 52' W., bet. secs. 9 and 16.

Over mountainous land, through scattered sagebrush.

3.80 Wash, 15 lks. wide, 1 ft. deep, drains N.

40.06 The ¼ sec. cor. of secs. 9 and 16, monumented with a granite stone, 16x14x8 ins. plainly mkd. ¼ on the N. face, firmly set 8 ins. in the ground, with a mound of stone N. of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T19N R44E
S 9
¼
S 16

1979

Bury the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. 89° 51' E., beginning new measurement.

Over mountainous land.

1.00 Trail road, bears NW. and SE.

36.60 Trail road, bears NNW. and SSE.

39.83 The cor. of secs. 8, 9, 16 and 17.

SUBDIVISION OF SECTION 1,
T. 19 N., R. 44 E., MDM, NEVADA
