160

SUBDIVISION OF SECTION 7, . 19 N., R. 45 E., MDM, NEVADA

| T. 19 N., R. 45 E., MDM, NEVADA |      |  |
|---------------------------------|------|--|
| СН                              | AINS | From the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.  |
|                                 |      | N. 0° 06' E., on the N. and S. center line of sec. 7.  |
|                                 |      | Over rolling land, covered with scattered sagebrush.   |
| 1                               | 9.96 | Point for the C-S 1/16 sec. cor. of sec. 7.  |
|                                 |      | Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with aluminum cap mkd.  |
|                                 |      | C<br>S 1/16 S 7<br>C   |
|                                 |      | 1979   |
|                                 |      | Set a wooden post, 6 ft. long, 6 ins. diam., 14 ins. in the ground, alongside the aluminum post.   |
| 3                               | 9.92 | Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E. and W. center line.  |
|                                 |      | Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.   |
|                                 |      | T19N R45E<br>C <sup>1</sup><br>S 7   |
|                                 |      | 1979   |
|                                 |      | Raise a mound of stone, 5 ft. base, 2 ft. high, W. of cor.   |
| 7                               | 9.84 | The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.  |
|                                 |      | From the E $\frac{1}{4}$ sec. cor. of sec. 7.  |
|                                 |      | N. 89° 26' W., on the E. and W. center line of sec. 7.   |
|                                 |      | Over rolling land, covered with scattered sagebrush.   |
| 4                               | 0.00 | The center $\frac{1}{4}$ sec. cor. of sec. 7.  |
| 6                               | 0.00 | Point for the C-W 1/16 sec. cor. of sec. 7.  |
|                                 |      | Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.   |
|                                 |      | $C - \frac{W 1/16}{S 7} C$   |
|                                 |      | 1979   |
|                                 |      | Set a wooden post, 6 ft. long, 3 ins. diam., 24 ins. in the ground, alongside the aluminum post.   |
| 7                               | 8.48 | The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the W.<br>bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$<br>ins. diam., firmly set and exposed 22 ins. above ground<br>in a mound of stone, with aluminum cap mkd. as<br>described in the field notes of the dependent resurvey<br>of T. 19 N., R. 44 E., executed concurrently under this<br>same group. |
|                                 |      |  |

8