

176

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 24 N., R. 49 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 24 N., R. 49 E., MDM, NEVADA

Reestablishment of the Survey Executed by  
D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors,  
in 1879,  
and the Resurvey Executed by  
Andrew Nelson, U. S. Surveyor,  
in 1927.

From the original cor. of Tps. 23 and 24 N., Rs. 49 and  
50 E., monumented with the decayed remains of a squared  
wooden post, in pieces, with illegible scribe marks  
visible, in the center of a circle of stone. This  
corner now refers to the cor. of T. 24 N., Rs. 49 and 50  
E. only.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T24N  
R49E R50E  
S 36 | S 31

1979

Reset the wooden post alongside the iron post and raise  
a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N.  $89^{\circ} 29'$  W., along the S. bdy. of sec. 36.

Over rolling land, through scattered sagebrush, heavy  
juniper and pinon pine.

9.90 Wash, 40 lks. wide, 3 ft. deep, drains NNW.

23.90 Trail road, bears NNW. and SSE.

39.89 The original  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, monumented  
with the decayed remains of a shaved wooden post, 10  
ins. long, 2 ins. diam., with illegible scribe marks  
visible, in the center of a circle of stone. This  
corner now refers to the  $\frac{1}{4}$  sec. cor. of sec. 36 only.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T24N R49E  
 $\frac{1}{4}$  S 36

1979

Reset the wooden post alongside the iron post and raise  
a mound of stone, 3 ft. base, 2 ft. high, N. of cor.