

205

DEPENDENT RESURVEY OF THE
FIFTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 56 E., MDM, NEVADA

CHAINS	<p>DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of a Portion of the Survey Executed by C. C. Tracy, U. S. Deputy Surveyor, in 1868, and a Portion of the Survey Executed by L. G. B. McDowell, U. S. Surveyor, in 1904.</p>
	<p>From the original standard cor. of secs. 32 and 33, monumented with the decayed remains of a squared wooden post, in pieces, in the center of a deeply embedded circle of stone, alongside a steel fence post.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T26N R56E <u>S 32 S 33</u></p> <p style="text-align: center;">1979</p>
	<p>Reset the wooden post and steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>N. 89° 46' W., along the S. bdy. of sec. 32.</p> <p>Over rolling land, through crested wheat grass; desc. 120 ft. over gradual W. slope.</p>
1.10	<p>The closing cor. of secs. 4 and 5, T. 25 N., R. 56 E., hereinafter described.</p>
39.93	<p>Point for the standard ¼ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">S C R26N R56E <u>¼ S 32</u></p> <p style="text-align: center;">1979</p>
40.92	<p>Descend 120 ft. over gradual W. slope to sec. cor.</p> <p>The N ¼ sec. cor. of sec. 5, T. 25 N., R. 56 E., hereinafter described.</p>