

DEPENDENT RESURVEY OF THE
FIFTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 56 E., MDM, NEVADA

CHAINS	
69.30	Fence, bears NNW. and SSE., enter scattered sagebrush.
70.20	Bladed road, bears NNW. and SSE.
79.86	The standard cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set and exposed 10 ins. above the ground, with brass cap mkd. as described in the field notes of the remonumentation of certain corners in T. 26 N., R. 56 E., executed under Group No. 393.
	N. 89° 46' W., along the S. bdy. of sec. 31.
	Over rolling land, through scattered sagebrush, juniper and pinon pine.
0.88	The closing cor. of secs. 5 and 6, T. 25 N., R. 56 E., hereinafter described.
23.00	Leave sagebrush, bears NE. and SW.; enter reseeded area.
39.91	Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C R26N R56E ¼ S 31 ----- 1979
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
40.79	The N ¼ sec. cor. of sec. 6, T. 25 N., R. 46 E., hereinafter described.
79.82	Point for the standard cor. of Tps. 25 and 26 N., Rs. 55 and 56 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T26N R55E R56E S 36 S 31 S 1 S 6 T25N ----- 1979
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.