

207

DEPENDENT RESURVEY OF THE  
FIFTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF R. 56 E., MDM, NEVADA

CHAINS

From this corner, the standard cor. of secs. 35 and 36, T. 26 N., R. 55 E., monumented with an iron post, 2 ins. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North, through R. 55 E., executed under Group No. 195, bears N. 89° 46' W., 79.82 chs. dist.

From this same corner, the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, T. 26 N., Rs. 55 and 56 E., monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 26 N., R. 55 E., executed concurrently under this same Group, bears N. 0° 24' W., 40.24 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
(THE RUBY VALLEY GUIDE MERIDIAN)  
T. 25 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
C. C. Tracy, U. S. Deputy Surveyor,  
in 1868.

From the original  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, monumented with the decayed remains of a squared wooden post, in pieces, in the center of a deeply embeded circle of stone, alongside a steel fence post.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T25N  
R55E R56E  
 $\frac{1}{4}$   
S 13|S 18

1979

Reset the wooden post and steel fence post alongside the iron post.

N. 0° 24' W., bet. secs. 13 and 18.

Over rolling land, through scattered sagebrush and rabbitbrush.

38.70 Fence, bears E. and W.

40.24 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.