

211

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 25 N., R. 56 E., MDM, NEVADA

CHAINS
80.17

Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T26N R56E} \\ \text{S } 32 \\ \hline \text{S } 51\text{S } 4 \\ \text{T25N} \\ \text{C C} \end{array}$$

1979

Set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 32 and 33, bears S. $89^{\circ} 46'$ E., 1.10 chs. dist.

From the cor. of secs. 8, 9, 16 and 17.

S. $89^{\circ} 50'$ W., bet. secs. 8 and 17.

Over rolling land, through scattered sagebrush, juniper and pinon pine.

39.93

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T25N R56E} \\ \text{S } 8 \\ \frac{1}{4} \hline \text{S } 17 \end{array}$$

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Leave scattered timber; edge, bears N. and S.

51.70

Bladed road, bears N. and S.

79.86

The original cor. of secs. 7, 8, 17 and 18, monumented with a wooden post, 12 ins. long, 1 in. square, with illegible scribe marks visible, loosely set 4 ins. in the ground.

At the corner point