CHAINS	
	From the cor. of secs. 5, 6, 7 and 8.
	N. 1° 13' W., bet. secs. 5 and 6.
	Over rolling land, through scattered sagebrush, juniper and pinon pine.
18.00	Trail road, bears E. and W.
26.00	Wash, 20 lks. wide, 2 ft. deep, drains W.
39.50	Fence, bears E. and W.
39.78	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, 3 ft. base, with brass cap mkd.
	T25N R56E ¼ S 6 | S 5 1979
80.16	Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T26N R56E S 31 S 6 | S 5 T25N CC 1979
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the standard cor. of secs. 31 and 32, bears S. 89° 46' E., 0.88 chs. dist.
	Point for the N ¼ sec. cor. of sec. 5 is on the Fifth Standard Parallel North and at midpoint bet. the closing cors. and on the N. bdy. of sec. 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.