

## T. 29 N., R. 23 E., MDM, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and the survey of the east boundary and subdivisional lines of Township 29 North, Range 23 East, Mount Diablo Meridian, Nevada and the retracement and remonumentation of certain corners of Mineral Survey Nos. 4036, 4323 and 4324.

The south boundary was surveyed by U.S. Surveyor W. A. Pray, in 1916, under Group No. 48. The west boundary was surveyed by U. S. Surveyor Walter H. Good, in 1928, under Group No. 117. Mineral Survey No. 4036 was surveyed by U.S. Mineral Surveyor Thos L. Darby, in 1911. Mineral Survey Nos. 4323 and 4324 were surveyed by U.S. Mineral Surveyor Milton A. Pray, in 1917.

Lines connecting the corner positions were run by random and true method. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 19, 1979.

The directions of the lines of this survey were determined by azimuth taken from U.S.G.S. triangulation station "WIND" and the southeast corner of T. 29 N., R. 23 E, occupied by U.S.G.S., in 1963. The vertical angles of measurements made on the slope were ascertained with a transit in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position for the southeast corner of township, occupied by U.S.G.S., in 1963, is at latitude  $40^{\circ} 19' 53.700''$  N. and longitude  $119^{\circ} 20' 15.601''$  W., as published by U.S.G.S.

The mean magnetic declination is  $18^{\circ}$  east.

DEPENDENT RESURVEY OF A PORTION OF  
THE SOUTH BOUNDARY,  
TOWNSHIP 29 NORTH, RANGE 23 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
W. A. Pray, U. S. Surveyor,  
in 1916.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 28 N., R. 23 E., executed under Group No. 48.