

Dependent Resurvey, Portion, E. Bdy.,
T. 28 N., R. 61 E., Mt. Diablo Mer., Nevada

CHAINS

T 28 N
R 61 E R 62 E
S 12 | S 7
S 13 | S 18
1963

North, bet. secs. 7 and 12.

Over nearly level land, through sagebrush.

19.60 Barbed wire fence, 3 strand, bears E. and W.

19.75 Trail Road, 10 lks. wide, bears E. and W.

20.04 Point for the S. 1/16 sec. cor. of secs. 7 and 12.

Set an iron post, 2½ ins. diam., 28 ins. long, 22 ins. in the ground, with brass cap mkd.

S 1/16
S 12 | S 7
1977

Set a 6 ft. long steel fence post alongside the iron post.

40.08 The ¼ sec. cor. of secs. 7 and 12, monumented with an iron post, 2½ ins. diam., firmly set, extending 8 ins. above ground, encircled by a collar of stone, 1 ft. base, to top, with brass cap mkd.

T 28 N
R 61 E R 62 E
¼
S 12 | S 7
1963

N. 0° 01' E., beginning new measurement.

Over rolling land, through sagebrush.

40.06 The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2½ ins. diam., firmly set, extending 10 ins. above ground, encircled by a collar of stone, 2½ ft. base, to top, with brass cap mkd.

T 28 N
R 61 E R 62 E
S 1 | S 6
S 12 | S 7
1963

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 N., R. 61 E., Mount Diablo Meridian, Nevada

(Restoring the 1882 survey by Monroe and McClellan
and the 1963 resurvey by Eldon W. Sibley)

From the true point for the cor. of sec. 1, 2, 35, and 36, on the S. bdy. of the tp.

N. 0° 07' W., bet. secs. 35 and 36.