

20

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 22 N., R. 40 E., MDM, NEVADA

CHAINS	
	<p>From the cor. of Tps. 21 and 22 N., Rs. 40 and 41 E., monumented with a trapstone, 14x13x13 ins., firmly set 4 ins. in the ground, mkd. with 6 grooves on the N., S., E. and W. faces, with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T22N R40E R41E <u>S 36 S 31</u> S 1 S 6 T21N</p> <p>1979</p> </div> <p>Deposit the original cornerstone alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>S. 89° 34' W., bet. secs. 1 and 36.</p> <p>Over gently rolling land, through medium sagebrush and bunchgrass.</p>
4.30	Trail road, bears NW. and SE.
23.50	Trail road, bears N. and S.
30.60	Wash, 30 lks. wide, 4 ft. deep, drains N.
40.26	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T22N R40E <u>S 36</u> ¹/₄ — S 1 T21N</p> <p>1979</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
42.20	Wash, 20 lks. wide, 2 ft. deep, drains NE.
80.52	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.