

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 22 N., R. 40 E., MDM, NEVADA

## CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

73.50 Wash, 30 lks. wide, 3 ft. deep, drains SW.

79.82 The cor. of Tps. 21 and 22 N., Rs. 39 and 40 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 N., R. 39 E., executed under Group No. 476.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 22 N., R. 40 E., MDM, NEVADA

Reestablishment of the Survey Executed by  
G. W. Conkling and T. K. Stewart,  
U. S. Deputy Surveyors,  
in 1881

From the cor. of Tps. 21 and 22 N., Rs. 39 and 40 E.

N.  $0^{\circ} 39'$  W., bet. secs. 31 and 36.

Over gently rolling land, through medium sagebrush and bunchgrass.

11.40 Trail road, bears ENE. and WSW.

29.80 Wash, 30 lks. wide, 4 ft. deep, drains WSW.

39.85 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T22N  
R39E R40E  
 $\frac{1}{4}$   
S 36|S 31

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

79.70 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.