## DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 23 N., R. 40 E., MDM, NEVADA

CHAINS 79.74

The cor. of Tps. 23 and 24 N., Rs. 39 and 40 E., monumented with a juniper post,  $1\frac{1}{2}$  ins. square, 10 ins. long, loosely set in a mound of earth, with illegible scribe marks visible. This corner was set by Conkling and Stewart under contract No. 132, which created a hiatus bet. T. 23 and 24 N., R. 40 E. Hereafter, this corner will refer to Tps. 23 and 24 N., R. 39 E., and Tps. 23 and  $23\frac{1}{2}$  N., R. 40 E.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T24N T23½N R39E | R40E S 36 | S 6 S 1 | S 6 R39E R40E T23N

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 23 N., R. 40 E., MDM, NEVADA

Reestablishment of the Survey Executed by G. W. Conkling and T. K. Stewart, U. S. Deputy Surveyors, in 1881.

From the cor. of Tps. 22 and 23 N., Rs. 40 and 41 E., monumented with an aluminum post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 7 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 22 N., R. 40 E., executed concurrently under this same group.

N. 0° 25' W., bet. secs. 31 and 36.

Over nearly level land, through medium budsage, shadscale and bunchgrass.

40.45 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T23N
R40E R41E  $\frac{1}{4}$ S 36|S 31

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.