DEPENDENT RESURVEY OF THE EAST BOUNDARY,

T. 23 N., R. 40 E., MDM, NEVADA CHAINS N. 0° 06' E., beginning new measurement. Over gently rolling land. The cor. of Tps. 23 and 24 N., Rs. 40 and 41 E., monumented with the remains of a juniper post, 1 in. 40.35 square, 13 ins. long, loosely set in a mound of earth, with illegible scribe marks visible. This corner was set by Conkling and Stewart under Contract No. 132, which created a hiatus bet. Tps. 23 and 24 N., Rs. 40 and 41 E. Hereafter, this corner will refer to Tps. 23 and $23\frac{1}{2}$ N., Rs. 40 and 41 E. At the corner point Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd. $T23\frac{1}{2}N$ R40E R41E <u> 1|S</u> 6 1|5 T23N 1979 Deposit the original wooden post alongside the aluminum post and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor. From this corner, the cor. of Tps. $23\frac{1}{2}$ and 24 N., Rs. 40 and 41 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground in a collar of stone, with brass cap mkd. as described in the field notes of T. $23\frac{1}{2}$ N., R. 41 E., executed concurrently under this same group, bears N. 41° 40' E., 28.83 chs. dist. DEPENDENT RESURVEY OF THE NORTH BOUNDARY. T. 23 N., R. 40 E., MDM, NEVADA Reestablishment of the Survey Executed by E. L. Bridges, U. S. Deputy Surveyor, in 1882. From the cor. of Tps. 23 and $23\frac{1}{2}$ N., Rs. 40 and 41 E. S. 88° 58' W_{\bullet} , along the N_{\bullet} bdy. of sec. 1. Over gently rolling land, through medium sagebrush, shadscale and bunchgrass. 40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this cor. will refer to sec. 1 only. Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.

Form 9600-10 (June 1978) (formerly 9180-7) USDI--BLM