## DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 23 N., R. 40 E., MDM, NEVADA

CHAINS

80.18

The cor. of secs. 5, 6, 31 and 32, monumented with a juniper post,  $1\frac{1}{2}$  ins. square, 10 ins. long, loosely set in a mound of earth, with illegible scribe marks visible. Hereafter, this cor. will refer to secs. 5 and 6 only.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.

S 6|S 5 T23N R40E

1979

Deposit the original wooden post alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

S.  $88^{\circ}$  49' W., along the N. bdy. of sec. 6.

Over rolling land, through medium sagebrush, shadscale and bunchgrass.

40.09 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Hereafter, this cor. will refer to sec. 6 only.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with aluminum cap mkd.

 $\frac{\frac{1}{4} \text{ S} + 6}{123 \text{N} + 123 \text{N}}$ 

1979

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

77.26 The cor. of Tps. 23 and 24 N., R. 39 E. and Tps. 23 and  $23\frac{1}{2}$  N., R. 40 E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 23 N., R. 40 E., MDM, NEVADA

Reestablishment of the Survey Executed by E. L. Bridges, U. S. Deputy Surveyor, in 1882.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an aluminum post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 22 N., R. 40 E., executed concurrently under this same group.