DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 16 S., R. 57 E., MDM, NEVADA

CHAINS

39.47

The $\frac{1}{4}$ sec. cor. of sec. 18, monumented with an iron post, 1 in. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 16 S., R. 56 E., executed under Group No. 50. Hereafter, this cor. will function as an angle point bet. secs. 13 and 18. Remark the brass cap to read as follows:

> A P T16S R56E \ R57E S 13 | S 18 1981 1917

N. 1° 08' W., beginning new measurement.

Over rolling land.

The cor. of secs. 12 and 13, T. 16 S., R. 56 E., 0.51 monumented with an iron post, 2 in. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 16 S., R. 56 E., executed under Group No. 50. Hereafter, this cor. will refer to the cor. of secs. 7, 12, 13 and 18. Remark the brass cap to read as follows:

> T16S R56E R57E S 12|S S 13|S 18

> > 1981 1917

INDEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA

This Independent Resurvey Supersedes the Survey Executed by R. H. Woods and W. H. Myrick, U. S. Deputy Surveyors, in 1881.

Point for the standard cor. of secs. 35 and 36, determined at 392.89 chs. in departure from the standard cor. of Tps. 16 S., Rs. 56 and 57 E., and EAST, from the original standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 16 S., R. 58 E.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with aluminum cap mkd.