

INDEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF R. 57 E., MDM, NEVADA

CHAINS

S C
T16S|R57E
S 35|S 36

1981

WEST, along the S. bdy. of sec. 35.

Over rolling land, through scattered undergrowth.

15.30 Trail road, bears WNW. and ESE.

19.33 The original standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 16 S., R. 58 E., identical with the U.S.C. & G.S. triangulation station "GLO NO. 2," monumented with a brass tablet, firmly set in the top of a concrete monument, exposed 6 ins. above the ground, with brass tablet mkd. as described in the published triangulation station data, and is at latitude $36^{\circ} 30' 27.021''$ N. and longitude $115^{\circ} 30' 46.981''$ W. Hereafter, this cor. will function as an angle point on the S. bdy. of sec. 35, T. 16 S., R. 57 E. Remark the brass tablet to read as follows:

A P
T16S R57E
S 35

1981

1926

Land, rolling.

Soil, sandy, gravelly and rocky.

Undergrowth, creosote brush, Spanish bayonet and Joshua trees.

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 57 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
R. H. Woods and W. H. Myrick, U. S. Deputy Surveyors,
in 1881, and

Partially Resurveyed by
T. A. Haig, U. S. Surveyor, in 1917.

The original standard corners will now function as angle points.

From the angle point on the S. bdy. of sec. 35, identical with U.S.C. & G.S. triangulation station "GLO NO. 2."

S. $89^{\circ} 59'$ W., along the S. bdy. of sec. 35.

Over rolling land.

20.67 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35.