

DEPENDENT RESURVEY OF  
THE FOURTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF R. 57 E., MDM, NEVADA

CHAINS	
39.99	<p>The original standard cor. of secs. 32 and 33, monumented with a limestone, 12x4x4 ins., firmly set in a mound of stone, plainly mkd. with 4 notches on the E. face and 2 notches on the W. face. Hereafter, this cor. will function as an angle point on the S. bdy. of sec. 31.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, 3 ft. base, with aluminum cap mkd.</p> <p style="text-align: center;">A P T16S R57E <u>S 31</u></p> <p style="text-align: center;">1981</p> <p>Bury the cornerstone alongside the aluminum post.</p> <hr/> <p>N. 89° 55' W., beginning new measurement.</p> <p>Over rolling land.</p>
13.84	<p>The standard cor. of Tps. 16 S., Rs. 56 and 57 E.</p> <p>Land, rolling. Soil, sandy, gravelly and rocky. Undergrowth, creosote brush, Spanish bayonet and Joshua trees.</p> <hr/> <p style="text-align: center;">INDEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">This Independent Resurvey Supersedes the Survey Executed by R. H. Woods, U. S. Deputy Surveyor, in 1881. A diligent search was made for the original corners, but none were found.</p> <hr/> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 01' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered undergrowth.</p>
6.45	<p>Point for the 80 1/16 sec. cor. of secs. 35 and 36, determined at 80.00 chs. in latitude from the cor. of secs. 25, 26, 35 and 36.</p>