DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH, THROUGH RANGE 20 EAST, MDM, NEVADA

	THROUGH RANGE 20 EAST, MDM, NEVADA
CHAINS	DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH, THROUGH RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by G. W. Garside, U. S. Deputy Surveyor, in 1878.
	From the standard cor. of Tps. 41 N., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., firmly set showing 10 ins. above ground, with a brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through Range 21 East, executed under Group No. 48.
	N. 89° 16' W., along the S. bdy. of sec. 36.
	Over rolling land, covered with sagebrush and bunchgrass.
10.94	Fall .227 chs. N. of a trap stone, 18x6x6 ins., firmly set in a mound of stone, mkd. with 6 notches on the E., W. and N. edges, with WCSC on the N. face. There is no record of this cor. and it does not correlate with other existing corners.
39.99	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a trap stone $18 \times 10 \times 6$ ins., firmly set 9 ins. in the ground, dimly mkd. $\frac{1}{4}$ on the N. face, with a mound of stone N.
	At the corner point
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.
	S C T41N R20E ½ S 36
	1980
	Deposit the original cornerstone alongside the aluminum post.
	N. 88° 43' W., beginning new measurement.
	Over rolling land.
39.36	Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.