

273

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 41 N., R. 20 E., MDM, NEVADA

<p>CHAINS 40.16</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T41N R20E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1981</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.</p>
<p>80.66</p>	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 42 N., R. 20 E., executed concurrently under this same group.</p>
<p>40.27</p>	<p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 18'$ E., bet. secs. 31 and 32.</p> <p>Over rolling land, covered with medium sagebrush and native grass.</p>
<p>40.27</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T41N R20E $\frac{1}{4}$ S 31 S 32</p> <p style="text-align: center;">1981</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.</p>
<p>80.54</p>	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>