

378

DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 19 E., MDM, NEVADA

CHAINS	
	<p>From the standard cor. of T. 41 N., Rs. 19 and 20 E., monumented with an unmarked trap stone, 30x14x10 ins., firmly set in a mound of stone. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">S C T41N R19E R20E <u>S 36 S 31</u></p> <p style="text-align: center;">1980</p> <p>Deposit the unmarked cornerstone and set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>From this corner, a U.S. Geological Survey triangulation station, monumented with a standard brass tablet, stamped, "BOULDER," firmly set in concrete in a drill hole in solid rock, bears S. 20° 42' W., 33.63 chs. dist.</p> <p>WEST, along the S. bdy. of sec. 36.</p> <p>Over rolling land, covered with sagebrush and bunchgrass.</p>
40.23	<p>Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">S C R41N R19E <u>¼ S 36</u></p> <p style="text-align: center;">1980</p> <p>Set a steel fence post, 5½ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
73.40	<p>Fence, bears N. and S.</p>
80.46	<p>Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a collar of stone, 3 ft. base to top, with aluminum cap mkd.</p>