

DEPENDENT RESURVEY OF THE
EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF R. 19 E., MDM, NEVADA

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with aluminum cap mkd.

S C
T41N R19E
S 32 | S 33

1980

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

S. $89^{\circ} 58'$ W., along the S. bdy. of sec. 32.

Over rolling land, covered with sagebrush, bunchgrass and scattered junipers.

39.98 The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a trap stone, 24x12x12 ins., firmly set in a mound of stone, dimly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

S C
T41N R19E
 $\frac{1}{4}$ S 32

1980

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 59'$ W., beginning new measurement.

Over rolling land, covered with sagebrush, bunchgrass and scattered juniper.

39.99 The standard cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set showing 13 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement and dependent resurvey of the Eighth Standard Parallel North, through a portion of R. 19 E., executed under Group No. 5.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside, U. S. Deputy Surveyor,
in 1878.
