

437

DEPENDENT RESURVEY OF A PORTION OF
THE EAST BOUNDARY,
T. 22 N., R. 43 E., MDM, NEVADA

CHAINS

The cor. of Tps. 21 and 22 N., Rs. 43 and 44 E.,
monumented with a granite stone, 11x11x9 ins., plainly
mkd. with 6 notches on the E., W., N. and S. edges,
firmly set 7 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T22N
R43E R44E
S 36 | S 31
S 1 | S 6
T21N

1979

Bury the original cornerstone alongside the iron post
and raise a mound of stone, 3 ft. base, 2 ft. high, S.
of cor.

This corner is a tellurometer traverse station occupied
under Group No. 389, Nevada, in 1961, and is at latitude
 $39^{\circ} 43' 26.707''$ N. and longitude $117^{\circ} 04' 40.409''$ W., as
published on Nevada Protraction Diagram No. 39, Unit No.
37.

From this corner, U-Station 37-6, monumented with a
copper-weld rod and brass top mkd. "BLM U-37-6 1961",
firmly set and exposed 6 ins. above the ground, bears N.
 $88^{\circ} 29'$ W., 38.23 chs. dist.

N. $0^{\circ} 35'$ E., bet. secs. 31 and 36.

Over gently rolling land, through sagebrush and
bunchgrass.

39.89

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a
quartzite stone, 10x5x5 ins., plainly mkd. $\frac{1}{4}$ on the W.
face, firmly set 5 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T22N
R43E R44E
 $\frac{1}{4}$
S 36 | S 31

1979

Bury the original cornerstone alongside the iron post
and raise a mound of stone, 3 ft. base, 2 ft. high, W.
of cor.
