453

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 22 N., R. 43 E., MDM, NEVADA

38.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T22N R43E S 1 S 12
	1979
76.64	Point for the cor. of secs. 1, 2, 11 and 12, determined latitudinally at record distance from the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp. and longitudinally at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T22N R43E S 2 S 1 S 11 S 12
	1979
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 2° 57' E., bet. secs. 1 and 2.
	Over rolling land, through sagebrush and bunchgrass.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
1	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	in the ground, with brass cap mkd.
	in the ground, with brass cap mkd. T22N R43E $\frac{1}{4}$
	in the ground, with brass cap mkd. T22N R43E \$\frac{1}{4}\$ S 2 S 1
71.00	in the ground, with brass cap mkd. T22N R43E \$\frac{1}{4}\$ S 2 S 1 1979 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
71.00 79.69	in the ground, with brass cap mkd. T22N R43E \$ 2 S 1 1979 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.