49

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 34 N., R. 59 E., MDM, NEVADA

	T. 34 N., R. 59 E., MDM, NEVADA
CHAINS 1.00	Draw, drains NNW.; asc. over W. slope.
11.80	Spur, slopes NNW.; desc. over NE. slope.
34.10	Ross Creek, 30 lks. wide, 1 ft. deep, course NW.; asc. over W. slope.
39.88	Point for the ½ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.
	T34N R59E 1 S 25 4 S 36
	1981
59.00	Ridge, bears NW. and ESE.; desc. over N. slope.
91.47	Point for the closing cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	T34N
	R59E R60E CC S 25 S 36 S 30
	1981
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	From this corner, the cor. of secs. 30 and 31, T. 34 N., R. 60 E., hereinbefore described, bears S. 0° 01' W., 9.49 chs. dist.
	Point for the E $\frac{1}{4}$ sec. cor. of sec. 36, is at midpoint bet. the closing cors. and on the W. bdy. of sec. 31, T. 34 N., R. 60 E.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	T34N R59E
	1/4 S 36
	1981
	From this corner, the W $\frac{1}{4}$ sec. cor. of sec. 31, T. 34 N., R. 60 E., hereinbefore described, bears S. 0° 01' W., 9.48 chs. dist.